PathGetShortPath

The destination string buffer must be long enough to hold the return file path

Sean Barnum, Cigital, Inc. [vita¹]

Copyright © 2007 Cigital, Inc.

2007-04-02

Part "Original Cigital Coding Rule in XML"

Mime-type: text/xml, size: 3876 bytes

Attack Category		Transfer as Impac		
	Path spoofing o	Path spoofing or confusion problem		
Vulnerability Category		Buffer Overflow		
	Unconditional			
Software Context	File Path Mana	File Path Management		
Location	• shellobj.h	• shellobj.h		
Description	The in/out destination string buffer of function PathGetShortPath() must be long enough to hold an expanded file path.			
	in place, to find the 'path specified. A sho 8.3 standards. Howe be relative, it is poss be longer that the input variable should be at in length.	The PathGetShortPath() modifies the path paramete in place, to find the "shortest path name" for the lor path specified. A short path is usually defined in 8.3 standards. However, since the input path might be relative, it is possible for the resulting path to be longer that the input path. Therefore, the path variable should be at least MAX_PATH characters in length. This routine is part of a deprecated shellobj.h modu that can be replaced with GetShortPathName.		
APIs	Function Name	Comme	ents	
	PathGetShortPath			
Method of Attack	to convert it to a sho However, it is not gu the original path due Therefore, the path b for expansion. Other	This routine modifies a path parameter IN PLACE to convert it to a short path name (8.3 format). However, it is not guaranteed to be shorter than the original path due to relative path expansion. Therefore, the path buffer must provide extra space for expansion. Otherwise, an attacker might be able to provide a path name that expands and overflows the buffer.		
Exception Criteria				
Solutions		olution escription	Solution Efficacy	

^{1.} http://buildsecurityin.us-cert.gov/bsi-rules/35-BSI.html (Barnum, Sean)

PathGetShortPath 1

	Whenever PathGetShortPathOszLongPath, is used. MAX_PATH characters in length. Consider replacing with GetShortPathName which takes separate in and out buffers. Effective. Effective.
Signature Details	void PathGetShortPath(LPWSTR pszLongPath);
Examples of Incorrect Code	<pre>WCHAR path[] = L".\\AShort\ \Path"; // Note: buffer is too small LPWSTR pszLongPath = path; PathGetShortPath(path);</pre>
Examples of Corrected Code	<pre>WCHAR path[MAX_PATH] = L".\\AShort \\Path"; // Note: buffer is correctly sized LPWSTR pszLongPath = path; PathGetShortPath(path);</pre>
Source Reference	http://msdn.microsoft.com/library/default.asp?url=/library/en-us/shellcc/platform/shell/reference/functions/pathgetshortpath.asp²
Recommended Resource	
Discriminant Set	Operating System • Windows
	Languages • C • C++

Cigital, Inc. Copyright

Copyright © Cigital, Inc. 2005-2007. Cigital retains copyrights to this material.

Permission to reproduce this document and to prepare derivative works from this document for internal use is granted, provided the copyright and "No Warranty" statements are included with all reproductions and derivative works.

For information regarding external or commercial use of copyrighted materials owned by Cigital, including information about "Fair Use," contact Cigital at copyright@cigital.com¹.

The Build Security In (BSI) portal is sponsored by the U.S. Department of Homeland Security (DHS), National Cyber Security Division. The Software Engineering Institute (SEI) develops and operates BSI. DHS funding supports the publishing of all site content.

2

mailto:copyright@cigital.com